

## STRAIGHT RECEPTION UNIT L. 120 CM PERSONALISED WITH LOGO OR SLOGAN

Collection ZOOM RECEPTION

<https://www.gautieroffice.com/zoom-reception/straight-reception-unit-l-120-cm-personalised-with-logo-or-slogan>



### Finishes :



Reference : 1U29P23

### Dimensions :

**W** : 120 | **H** : 112/74 | **D** : 74/85

**W** : 48 | **H** : 44/30 | **D** : 30/34

### Technical description :

**STRUCTURE** • Furniture: structure in particleboard covered with white paper, edges same finish. • Reception desks: Melamine-coated particleboard body white. • Sides, top and shelves of banks, intermediate storage and reception plans suitable for disabled: chipboard melamine oak or cherrywood decor, ABS 1 and 2 mm edges oak or cherrywood decor. • Mobile pedestal units 2 and 3 drawers: RAL.9003 epoxy lacquered steel. Pen in gray PS in the mass. Black casters • Top option for mobile pedestal units: made of particleboard Thickness 18mm for options covered with melamine oak, cherrywood and white Thickness 12 mm covered with a foam and a fabric (100% polyester, 330gr/m<sup>2</sup>) orange or green or pink or blue and equipped with two magnetic strips for installation on metal boxes.

**OTHER ELEMENTS** Furniture: • Handles in white lacquered ABS. • Clear tempered glass 4 mm glass doors. • Sliding profile in natural anodized aluminum. • Anthracite ABS guide profile in the mass. • Simple lock, multi-variatal. Reception desk: • Cable tidy and cable tray in ABS lacquered grey or white in the mass. • Drawer frames made of particleboard with textile imitation effect, mounted on grey roller slides. • Drawer for suspended files standar for France and USA. Handles in white ABS in the mass. • Furniture to self-assembly except those reported with \* (fully assembled except possibly handles, skates and castors).

**ECOLOGY** To ensure an ever cleaner environment, our company has developed low-emission panels. This collection is manufactured with wood panels containing less than 4 mg/100 g of formaldehyde - two times less than the top European standard (EN 13986).